

STONE TECHNOLOGIES, CORP.
PO BOX 2161, CLEVELAND, TN 37320-2161
TEL. (423) 503 4490 FAX. (425) 732 0920
www.stonetechnologiesinc.com

CONCRETE SEALER X-5

WATER-BASED

Forms a low gloss water and stain repellent barrier on all types of concrete, mortar, masonry and brick surfaces.

Directions: Stir well before using. Brush, roll (3/8" nap) or spray using an airless sprayer onto the concrete. Always remove any excess from the surface and never allow the product to puddle or accumulate on the surface. Apply the second coat after 4 to 6 hours. Allow to air dry for 24 hours and avoid heavy traffic for 48 hours.

WARNING: *Keep out of reach of children and animals.
Always wear gloves and protective goggles when using this product.*

1 Gallon (3.78L)

1.FIRST AID

Eyes: Flush with cool water for at least 15 minutes. Call a physician.

Skin: Wash thoroughly with soap and water. Call a physician.

Ingestion: Call a physician. Never give anything by mouth to an unconscious person.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration preferably mouth to mouth. Call a physician.

2.SPILL CONTROL

Eliminate all ignition sources and keep public away. Recover free product with absorbent materials and dispose of in accordance with local, State and Federal Regulations. Keep product out of sewers and water courses.

3. PROTECTIVE EQUIPMENT

Wear safety glasses or goggles and recommended protective gloves.

If exposure exceeds TLV, wear NIOSH/MSHA approved respirator.

4. PRECAUTIONS

Do not get in eyes, on skin or clothing. Do not take internally.

Wash thoroughly after handling.

5. GENERAL INSTRUCTIONS

Before using this product read Material Safety Data Sheet (MSDS).

An MSDS is available upon request from Stone Technologies, Corp.

Note: Emptied container retains vapor or product residue.

HMIS Rating: H = 1, F = 1, R = 0, PP = X

For emergency health and safety information contact: (423) 503 4490

DISCLAIMER

The information contained herein is based on data available to us and is believed to be accurate. However, Stone Technologies, Corp. makes no express or implied warranty of merchantability or fitness for a particular use. Handling, storage and use of this product by the buyer or user are beyond the control of Stone Technologies, Corp. Risks such as ineffectiveness or other unintended consequences resulting from but not limited to failure to follow label directions will be assumed by the buyer or user. In no case will seller be held liable for consequential, special or indirect damages resulting from the handling, storage or use of this product.